

Briton

لیست محصولات

تحت شبکه پروژه‌ای برایتون


اسفند ماه ۱۴۰۳



IP Camera

8MP

1. IPC-6A813B2A-TPL



H.265+ 8MP Network Camera 1/ 2.8" Sony CMOS Starlight
2.8 mm Fixed Lens @F2.0
 H.264+(Ultra H.264), H.265+ (Ultra H.265)
 30fps@ 8MP(3840*2160), 30fps@ 6MP, 30fps@ 4MP, 90fps@ 2MP
Alarm I/O:1/1,DC12V,Built-in POE
 Triple Stream (Video Bit Rate:11 Kbps~16 Mbps)
 IP67, IK10, 6KV Surge Protection



2. IPC-6A813D90-TPM



H.265+ 8MP Network Camera 1/ 2.8" Sony CMOS Starlight
2.8 mm Fixed Lens @F1.6
30fps@ 8MP(3840*2160), 30fps@ 6MP, 30fps@ 4MP, 60fps@ 2MP
Built in Mic(Optional), **Alarm I/O**,DC12V,Built-in POE
 Triple Stream (Video Bit Rate:11 Kbps~16 Mbps)
 IP67, IK10, 6KV Surge Protection




3. IPC-6A813C37-TPLZ



H.265+ 8MP Network Camera 1/ 2.8" Sony CMOS Starlight
 Smart IR,120db WDR,2D/3D DNR ; Audio I/O:1/1, Mobile Surveillance
 2.7~13.5 mm @F1.6 Motorized Fast Auto Focus Lens
IR range 70-80m
 H.264+(Ultra H.264), H.265+ (Ultra H.265)
 30fps@ 8MP(3840*2160), 30fps@ 6MP, 30fps@ 4MP, 90fps@ 2MP
 Audio I/O, **Built in Mic(Optional)**, **Alarm I/O**,DC12V,Built-in POE
 Triple Stream (Video Bit Rate:11 Kbps~16 Mbps)
 IP67, IK10, 6KV Surge Protection
 Size: 74.5x219mm Gross Weight: 900g




4. IPC-6A813E90-TPMLZ



H.265+ 8MP Network Camera 1/ 2.8" Sony CMOS Starlight
 Smart IR,120db WDR,2D/3D DNR ; Audio I/O:1/1, Mobile Surveillance
 2.7~13.5 mm @F1.6 Motorized Fast Auto Focus Lens
IR range 50-60m
 30fps@ 8MP(3840*2160), 30fps@ 6MP, 30fps@ 4MP, 60fps@ 2MP
 Audio I/O, **Built in Mic**, **Alarm I/O**,DC12V,Built-in POE
 Triple Stream (Video Bit Rate:11 Kbps~16 Mbps)
 IP67, IK10, 6KV Surge Protection
 Size: Φ142x113.4 mm Gross Weight: 935g



5. IPC-6A823E90-TPMLZ



H.265+ 8MP Network Camera 1/1.8" Sony CMOS Super Starlight
 Smart IR,120db WDR,2D/3D DNR ; Mobile Surveillance
 2.7~13.5 mm @F1.4 Motorized Fast Auto Focus Lens
IR range 60-70m
 30fps@ 8MP(3840*2160), 30fps@ 6MP, 30fps@ 4MP,60fps@ 2MP
 Audio I/O, **Built in Mic**, **Alarm I/O**,DC12V,Built-in POE
 Triple Stream (Video Bit Rate:11 Kbps~16 Mbps)
 IP67, IK10, 6KV Surge Protection
 Size: Φ141*119 mm Gross Weight: 1.2Kg



6. IPC-6A823C37-TPMLZ




H.265+ 8MP Network Camera 1/1.8" Sony CMOS Super Starlight
 Smart IR,120db WDR,2D/3D DNR ; Mobile Surveillance
 2.7~13.5 mm @F1.4 Motorized Fast Auto Focus Lens
IR range 80-90m
18 Smart function, Heat Map
 30fps@ 8MP(3840*2160), 30fps@ 6MP, 30fps@ 4MP,60fps@ 2MP
 Audio I/O, **Built in Mic**, **Alarm I/O**,DC12V,Built-in POE
 Triple Stream (Video Bit Rate:11 Kbps~16 Mbps)
 IP67, IK10, 6KV Surge Protection
 Size: Φ265*100 mm Gross Weight: 1.4Kg



Dual-Lens (180° Panoramic)

6. IPC-6A812B61-TPMSCD




Dual 4MP Network Camera 1/ 1.8" Progressive scan CMOS Sensor ,Full color
4.0mm Fixed Lens @F 1.0 ,Full color Image Performance
H.264 ,H.264+,H.265 ,H.265+
Triple Stream **20fps@ 8MP(5120*1440)**
Red & blue light warning ,Sound warning
Dual internal Mic , internal Speaker , 140db WDR
Alarm I/O:1/1,Audio I/O:1/1 , DC12V,Built-in POE
IP67, IK10, 6KV Surge Protection



Fisheye

7. IPC-4A613F01-TPMS



H.265+ 6MP Network Camera 1/ 1.2.5" Progressive scan CMOS Sensor
1.68 mm Fixed Lens @F2.0
Fisheye 6MP (2560*2560 @30Fps)
4CH@ePTZ (640*480 @30Fps)
Fisheye+ Panoramic+3CH@ePTZ (2560*2560+ 1920*1080+640*480 @30Fps)
Fisheye + 4CH @ ePTZ (2560*2560+640*480@30 Fps)
Panoramic + 4CH @ ePTZ (2560*2560+640*480@30 Fps)
Panoramic (2560*2560 @30Fps)
Built in Mic , internal Speaker , 120 db WDR
Alarm I/O:1/1,Audio I/O:1/1 , DC12V,Built-in POE
6 Streams Transmission
IP67, IK10, 6KV Surge Protection



Speed dome

8. IPD-6108Q04-TPZ



H.265+ **8MP** (Sony) Progressive scan Cmos Sensor (1/1.8"), **Super Starlight 38X** High Speed Dome, Optical Lens (6~228 mm), 2D/3D DNR, **WDR 120dB**
Triple Stream: **30fps@8MP(3840*2160)**, 30fps@6MP,, 30fps@2MP
Dual-Core ARM Cortex A7@900MHz
Smart Motion Detection (Human & Vehicle)
250~260 m Smart IR SMD
Support POE, **SD Slot up to 256GB, Audio: 1/1, Alarm: 1/1**
IP67, 6KV Surge Protection



9. IPD-69513Q81-FP



H.265+ **5MP** (Sony) Progressive scan Cmos Sensor (1/2.8"), **Starlight 32X** High Speed Dome, Optical Lens (4.8~154 mm), 2D/3D DNR, **WDR 120dB**
Triple Stream: 20fps@5MP, 25/30fps@720P, 25/30fps@CIF
Smart Motion Detection (Human & Vehicle)
Perimeter Protection : line crossing , intrusion (Human & Vehicle)
Basic Analysis , Onvif, Profile S, CGI, Mobile Surveillance
Support POE, **SD Slot up to 256GB, Audio: 1/1, Alarm: 1/1**
Up to 250M Smart IR SMD Technology
IP66, 6KV Lightning Protection



10. IPD-6N25AQ61P-FP



H.265+ **2MP** (Sony) Progressive scan Cmos Sensor (1/2.8"), **Starlight 25X** High Speed Dome, **Optical Lens (4.7~118 mm)**, 2D/3D DNR, **WDR 120dB**
Triple Stream: 25/30fps@2M, 25/30fps@D1, 25/30fps@CIF
Basic Analysis , Onvif, Profile S, CGI,
Mobile Surveillance , Support POE,
SD Slot up to 128GB
Audio: 1/1, Alarm: 1/1
Up to 100M Smart IR SMD Technology
IP66, 6KV Lightning Protection



5MP

9. IPC-414557B1A-TMU



H.265+ 5MP Network Camera 1/ 2.7" CMOS Starlight
Smart IR,120db WDR,2D/3D DNR ; Mobile Surveillance
5 Smart Functions + Face Detection
Triple Stream: 25fps@5MP, 25fps@4MP,25fps@1080P
Onvif, Profile S, CGI
Dual light:2pcs Array LED*2pcs Warm light/ IR range 30m
Fixed focal Lens , 3.6mm
SD Card Support 128GB,Reset Button ,DC12V,Built-in POE , Built in Mic
IP67 , Metal Housing Size: 68x172.3mm

Gross Weight: 490g



10. IPC-414557C2C-TAMLZ



H.265+ 5MP Network Camera 1/ 2.7" CMOS
Smart IR,120db WDR,2D/3D DNR ; **Audio I/O:1/1** ,Mobile Surveillance
5 Smart Functions +**Face detection**
Triple Stream: 25fps@5MP, 25fps@4MP,25fps@1080P
Onvif, Profile S, CGI
4pcs Array LED/ **IR range 50m,Strobe light**
Motorized Lens , 2.7-13.5mm
SD Card Support 128GB,Reset Button ,DC12V,Built-in POE , **Built in Mic**
IP67 , Metal Housing Size: 86x215.3mm

Gross Weight: 875g



11. IPC-6N513C2C-TP(M)LZ



H.265+ 5MP Network Camera 1/ 2.8" CMOS Starlight
Smart IR,120db WDR,2D/3D DNR ; Audio I/O:1/1, Mobile Surveillance
16 Smart Functions include **Face Detection + People counting**
Triple Stream: 30fps@5MP, 25fps@720P,25/30fps@CIF
Onvif, Profile S, CGI
4pcs Array LED/ **IR range 70m,Strobe light**
Motorized Lens , 2.7-13.5mm,F1.6
SD Card Support 128GB, Alarm I/O:1/1,DC12V,Built-in POE , **Built in Mic (M) Series**
IP67 , Metal Housing , Reset Button Size: 74.5x219mm

Gross Weight: 900g



12. IPC-414557E89C-TAMLZ




H.265+ 5MP Network Camera 1/ 2.7" CMOS
Smart IR,120db WDR,2D/3D DNR ; **Audio I/O:1/1** ,Mobile Surveillance
5 Smart Functions +**Face detection**
Triple Stream: 25fps@5MP, 25fps@4MP,25fps@1080P
Onvif, Profile S, CGI
4pcs Array LED/ **IR range 50m,Strobe light**
Motorized Lens , 2.7-13.5mm
SD Card Support 128GB,Reset Button ,DC12V,Built-in POE , **Built in Mic**
IP67 , Metal Housing Size: Φ142x113.4 mm

Gross Weight: 935g



13. IPC-6N513E89C-TP(M)LZ



H.265+ 5MP Network Camera 1/ 2.8" CMOS Starlight
Smart IR,120db WDR,2D/3D DNR , Mobile Surveillance
16 Smart Functions include **Face detection+People Counting**
Triple Stream: 25/30fps@5MP, 25/30fps@1080P,25/30fps@720P,25/30fps@CIF
Onvif2.6, Profile S, CGI
4pcs Array LED/ **IR range 50m,Strobe light**
Motorized Lens , 2.7-13.5mm ,F1.6
SD Card Support 128GB,Alarm I/O:1/1,DC12V,Built-in POE , Built in Mic (M) Series
IP67 , Metal Housing,IK10 , DC12V,Built-in POE Size: 142x113.4mm Gross Weight: 980g



2MP

15. IPC-714211C2C-TALZ



H.265+ 2MP Network Camera 1/ 2.8" CMOS Starlight
Smart IR,120db WDR,2D/3D DNR ; Audio I/O: 1/ 1,
Mobile Surveillance
5 Smart Functions
Triple Stream: 25/ 30fps@2MP, Onvif2.6, Profile S, CGI
4pcs SMD LED/ IR range 50m
Motorized Lens , 2.7-13.5mm
IP67, Metal Housing SD Card support 128GB
DC12V,Built-in POE Size: 74.5x218.9mm



Gross Weight: 870g

16. IPC-714211E89-TMZ



H.265+ 2MP Network Camera 1/ 2.8" CMOS Starlight
Smart IR,120db WDR,2D/3D DNR ; Audio I/O: 1/ 1,
Mobile Surveillance
5 Smart Functions
Triple Stream: 25/ 30fps@2MP, Onvif2.6, Profile S, CGI
4pcs SMD LED/ IR range 40m
Motorized Lens , 2.7-13.5mm
IP67, Metal DC12V,Built-in POE
Size: 142x114.9mm



Gross Weight: 950g

NVR

1. NVR-6CB16P-N53




16CH H.265+ 4K NVR **Bandwidth I/O:160M/256M**
 16CH IP Video input, up to 12MP 16ch 1080P Playback
 cloud storage/ cloud upgrade/smart playback
 15 Smart functions + Face detection + Parking detection+ People counting
 SMD , Audio I/O:1/ 1; **Alarm I/O:8 /1**
 HDMI, VGA, **SATA*2(10T HDD)**, 3G/4G, WIFI
 Remote Control , USB Mouse, DC12V/5A Adapter
 Dimension:380 x 305 x 45mm



2. NVR-6B32EP-W27-4H




32CH H.265+ 4K NVR **Bandwidth I/O :256M/256M**
 Support 12MP/8MP/5MP/4MP/3MP/1080P/720P Cameras
 32ch 8MP Record/4ch 8MP Playback
 cloud storage/ cloud upgrade/smart playback
 15 Smart functions + Face detection + Parking detection+ People counting
 32ch 1080P Record/16ch 1080P Playback
 Audio I/O:1/ 2; **Alarm I/O:16 /4**
 1*RS485 1*HDMI, VGA,**SATA*4(10T HDD)**, 3G/4G,WIFI
 Remote Control , USB Mouse,AC100~240V
 Dimension:440(W)×452(D)×90(H)mm



3. NVR-6CB32P-W26-8H




32CH H.265+ 4K NVR **Bandwidth I/O:256M/256M**
 Support 12MP/8MP/5MP/4MP/3MP/1080P/720P Cameras
 32ch 8MP Record/4ch 8MP Playback /32ch 8MP Recording/16ch 1080P Playback
 cloud storage/ cloud upgrade/smart playback
 15 Smart functions + Face detection + Parking detection+ People counting
 Audio I/O:1 /2;**Alarm I/O:16 /4**
2*RS485 2*HDMI,VGA,SATA*8(10T HDD),eSATA*1,3G/4G,WIFI
 Remote Control , USB Mouse,AC100~240V
 Dimension:440(W)×452(D)×90(H)mm



4. NVR-6B64P-W26-8H




64CH H.265+ 4K NVR **Bandwidth I/O:320M/256M**
 Support 12MP/8MP/5MP/4MP/3MP/1080P/720P Cameras
 64ch 8MP Record/4ch 8MP Playback
 64ch 8MP Recording/16ch 1080P Playback
 cloud storage/ cloud upgrade/smart playback
 15 Smart functions + **Face detection**
 + Parking detection+ People counting
 Audio I/O:1 /2;**Alarm I/O:16 /4;2*RS485**
2*HDMI,VGA,SATA*8(10T HDD),eSATA*1,3G/4G,WIFI
 Remote Control , USB Mouse,AC100~240V
 Dimension:440(W)×452(D)×90(H)mm



5. NVR-6B32SP-W28-8H




32CH H.265+ 4K NVR **Bandwidth I/O:256M/256M**
 Support 12MP/8MP/5MP/4MP/3MP/1080P/720P Cameras
 16CH Sync Playback(Up to 4K@30fps)
 2 * RJ45(10/100/1000Mbps)+LED Indicator
2 *Gigabit SFP Port
 cloud storage/ cloud upgrade/smart playback
 15 Smart functions + **Face detection** + Parking detection+ People counting
 Audio I/O:1 /1;**Alarm I/O:16 /4;2*RS485**
2*HDMI,VGA,SATA*8(14T HDD),eSATA*1,3G/4G,WIFI
 Remote Control , USB Mouse,AC200~240V
 Dimension:440(W)×452(D)×90(H)mm



6. NVR-6B32RP-W26-8H




32CH H.265+ 4K NVR **Bandwidth I/O:256M/256M**
Support 12MP/8MP/5MP/4MP/3MP/1080P/720P Cameras
16CH Sync Playback(Up to 4K@30fps)
2 * RJ45(10/100/1000Mbps)+LED Indicator
Raid 0-1-3-5-10
cloud storage/ cloud upgrade/smart playback
15 Smart functions + **Face detection** + Parking detection+ People counting
Audio I/O:1 /1 ; **Alarm I/O:16 /4 ; 2*RS485**
2*HDMI,VGA,SATA*8(14T HDD),e SATA*1,3G/4G,WIFI
Remote Control , USB Mouse,AC200~240V
Dimension:440(W)×452(D)×90(H)mm



7. NVR-6B64SP-W28-8H




64CH H.265+ 4K NVR **Bandwidth I/O:320M/256M**
Support 12MP/8MP/5MP/4MP/3MP/1080P/720P Cameras
16CH Sync Playback(Up to 4K@30fps)
2 * RJ45(10/100/1000Mbps)+LED Indicator
2 *Gigabit SFP Port
cloud storage/ cloud upgrade/smart playback
15 Smart functions + **Face detection** + Parking detection+ People counting
Audio I/O:1 /1;**Alarm I/O:16 /4;2*RS485**
2*HDMI,VGA,SATA*8(14T HDD),e SATA*1,3G/4G,WIFI
Remote Control , USB Mouse,AC200~240V
Dimension:440(W)×452(D)×90(H)mm



8. NVR-6B64RP-W28-8H




64CH H.265+ 4K NVR **Bandwidth I/O:320M/256M**
Support 12MP/8MP/5MP/4MP/3MP/1080P/720P Cameras
16CH Sync Playback(Up to 4K@30fps)
2 * RJ45(10/100/1000Mbps)+LED Indicator
Raid 0-1-3-5-10
cloud storage/ cloud upgrade/smart playback
15 Smart functions + **Face detection** + Parking detection+ People counting
Audio I/O:1 /1;**Alarm I/O:16 /4;2*RS485**
2*HDMI,VGA,SATA*8(14T HDD),e SATA*1,3G/4G,WIFI
Remote Control , USB Mouse,AC200~240V
Dimension:440(W)×452(D)×90(H)mm



9. NVR-6B64SRP-W28-8H



64CH H.265+ 4K NVR **Bandwidth I/O:320M/256M**
Support 12MP/8MP/5MP/4MP/3MP/1080P/720P Cameras
16CH Sync Playback(Up to 4K@30fps)
2 * RJ45(10/100/1000Mbps)+LED Indicator
2 *Gigabit SFP Port
Raid 0-1-3-5-10
cloud storage/ cloud upgrade/smart playback
15 Smart functions + **Face detection** + Parking detection+ People counting
Audio I/O:1 /1;**Alarm I/O:16 /4;2*RS485**
2*HDMI,VGA,SATA*8(14T HDD),e SATA*1,3G/4G,WIFI
Remote Control , USB Mouse,AC200~240V
Dimension:440(W)×452(D)×90(H)mm



10. NVR-6B64SRP-W38-16H



64CH H.265+ 4K NVR **Bandwidth I/O:320M/256M**
Support 12MP/8MP/5MP/4MP/3MP/1080P/720P Cameras
16CH Sync Playback(Up to 4K@30fps)
2 * RJ45(10/100/1000Mbps)+LED Indicator
2 *Gigabit SFP Port
Raid 0-1-3-5-10
cloud storage/ cloud upgrade/smart playback
15 Smart functions + **Face detection** + Parking detection+ People counting
Audio I/O:1 /1;**Alarm I/O:16 /4;2*RS485**
2*HDMI,VGA,Hotswap,SATA*16(14T HDD),e SATA*1,3G/4G,WIFI
Remote Control , USB Mouse,AC200~240V
Dimension:485*435*145 mm



11. NVR-6B128SRP-W38-16H



128CH H.265+ 4K NVR **Bandwidth I/O:1024M/800M**
Support **32MP, 16MP, 12MP, 8MP, 5MP, 4MP, 3MP, 1080P, 720P**
VGA, 4CIF, DCIF, 2CIF, CIF, QCIF
32CH 1080P@30fps, 16CH 4Mp@30fps
3xRJ45/ 1x2.5GE Or 3x self-adaptive Ethernet interface,
(10/100/1000Mbps)+LED Indicator
2 * Gigabit SFP Port
Raid 0-1-5-6-10-50-60
cloud storage/ cloud upgrade/smart playback
15 Smart functions + **Face detection** + Parking detection+ People counting
Audio I/O:1 /2;**Alarm I/O:16 /8;2*RS485**
4*HDMI,2*VGA,Hotswap,SATA*16(22TB HDD),e SATA*2,3G/4G,WIFI
Remote Control , USB Mouse,AC200~240V
Dimension:485*435*145 mm



SWITCH

1. BSW-2618SCF0-OR

28 Port L2/L3 Switch , 10/100/1000 Base
Uplink port: 16 *1G SFP , 4*10G SFP , 8*1G RJ45
 Bandwidth Support:128GB
 Web, SSH , Telnet , Console Management
 Dual Power Input , AC200~240V
 Metal Case,IP51 , Rackmount, Dimension:440*179*45 mm



2. BSW-1608SNC1-315R

16 Port L2+ POE Switch , 10/100/1000 Base
POE out put 315 watt
Ports: 8*1G POE RJ45
 Uplink Port :4*1G RJ45 , 4*1G SFP
 Bandwidth Support:20GB
 Web, SSH , Telnet , Console Management
 Dual Power Input , External Power 48-54V
 Metal Case,IP51 , Dimension:202*130*66 mm



3. BSW-1005SNCFO-120RD

10 Port POE Switch , 10/100/1000 Base
POE out put 120 watt
Ports: 4*1G POE RJ45
 Uplink Port :3*1G RJ45 , 2*1G SFP
 1*Power transmit RJ45
 Bandwidth Support:18.2GB
 Web Management, AC200~240V
 Metal Case,IP51 , Dimension:250*105*45 mm

