

## UVR-7TAB08AH-D18A

### 8 Channels 1U 1HDD Digital Video Recorder



### Key Features

- H.265+/H.265 dual-stream video compression
- Supports HDCVI/AHD/TVI/CVBS/IP video inputs
- Up to 8 channels Smart Motion Detection
- Up to 1 channels Perimeter Protection
- Up to 1 channels Face Detection
- Up to 1 channels Line crossing detection & Intrusion detection
- Audio I/O : 1/1
- Total Bandwidth : 80Mbps
- Dual streaming recording
- All channel audio over coaxial
- Max 10 channels IP camera input, up to 5M

### Smart Functions

- Smart Motion Detection (based on Human&Vehicle)
- Perimeter Protection (based on Human&Vehicle)
- Smart Detection for Analog (Line crossing detection, Intrusion detection, Face Detection)

### Compression and Recording

- H.265+/H.265 dual-stream video compression
- Support 8ch 5M lite 10fps encoding

### HD Video Output

- Support HDMI, VGA, CVBS



## Storage and Playback

- 1 SATA interface (up to 8 TB capacity per HDD)
- 8ch 5M lite 10fps playback

## Network & Ethernet Access

- 1 RJ-45 10/100 M self-adaptive Ethernet interface

## Third-party Cloud

- Support Google Drive & Dropbox Cloud storage
- Support Cloud upgrade

## Specification

| Video & Audio Input  |  |
|----------------------|--|
| Video Input          | 8-ch BNC interface (1.0Vp-p, 75 fi)  |
| TVI                  | 5MP, 4MP, 1080P, 720P  |
| CVI                  | 4MP, 1080P, 720P   |
| AHD                  | 5MP, 4MP, 1080P, 720P  |
| CVBS                 | Support  |
| IPC                  | Up to 5MP in full IP mode  |
| Audio Input          | 1-ch RCA (2.0Vp-p, 1kfi)   |
|                      | 8-ch via coaxial cable   |
| Two-way talk         | Reuse the first audio input  |
| Video & Audio Output |  |
| HDMI                 | 1-ch, resolution: 4K (3840 × 2160)/30Hz, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz |
| VGA                  | 1-ch, resolution: 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz                        |
| CVBS                 | 1-ch, BNC (1.0Vp-p, 75 fi), resolution: PAL: 704 × 576, NTSC: 704 × 480                      |
| Audio Output         | 1-ch, RCA (Linear, 1kfi)   |
| Recording            |  |
| Compression          | H.265/H.265+/H.264/H.264+  |
| Resolution           | 8-ch 5MP Lite @ 10fps;   |
|                      | 8-ch 4MP Lite/1080P @ 15fps;   |
|                      | 1080P Lite @ 25fps   |
|                      | 720P/960H/D1/CIF real time   |




|                              |  |
|------------------------------|--|
| Frame Rate (fps)             | 1-25fps (PAL) /30fps (NTSC)  |
| Video Bit Rate               | 11Kbps ~ 4026Kbps  |
| Audio Compression            | G.711a   |
| Audio Bit Rate               | 64kbps   |
| <b>Playback &amp; Backup</b> |  |
| Playback Mode                | Smart/Normal/Time Division/Label/Event/Picture Playback  |
| Playback Rate                | 8-ch Playback  |
| Backup Mode                  | USB Device/Network   |
| <b>Smart Function</b>        |  |
| SMD Plus                     | 8-ch SMD Plus based on Human and Vehicle   |
| PP                           | 1-ch PP based on Human and Vehicle   |
| Smart Detection for Analog   | 1-ch Line crossing detection, Area Intrusion detection<br>1-ch Face Detection  |
| VQD                          | N/A  |
| Smart Detection for QV IPC   | Line crossing detection, Area Intrusion detection  |
| Smart Playback for Analog    | Line crossing detection, Area Intrusion detection, Motion Detection, Face Detection                                      |
| Smart Playback for QV IPC    | Line crossing detection, Area Intrusion detection, Motion Detection  |
| Cloud Storage                | Support  |
| Cloud Upgrade                | Support  |
| <b>Network</b>               |  |
| Ethernet                     | 1 RJ-45 10/100Mbps self-adaptive Ethernet interface  |
| Network Function             | HTTPs, HTTP, TCP/IP, IPv4, UPnP, Onvif 2.6, RTSP, RTCP, UDP, SMTP, SNMP, Multicast, IGMP, NTP, DHCP, DNS, DDNS, FTP, P2P |
| Smart Phone                  | IOS (iPhone, iPad) , Android (Phone, Pad)  |
| <b>Hard Disk</b>             |  |
| SATA                         | 1 HDD  |
| Capacity                     | Up to 8TB capacity for each HDD  |
| <b>External Interface</b>    |  |
| Serial Interface             | N/A  |
| USB Interface                | Front panel: 1 × USB 2.0<br>Rear panel: 1× USB 2.0   |
| Alarm Input                  | N/A  |
| Alarm Output                 | N/A  |
| <b>General</b>               |  |




|                       |   |
|-----------------------|---|
| Power Supply          | DC12V, 2A                                       |
| Power Consumption     | ≤10W (without HDD)                              |
| Working Environment   | 14°F ~ 131°F (-10°C ~ 55°C) Humidity 10% to 90% |
| Dimension (W × D × H) | 250 × 230 × 45 mm (9.84" × 9.06" × 1.77")       |
| Weight (without HDD)  | 1.2 kg (2.64 lb)                                |

## Dimensions



## Rear Panel



| No. | Description  | No. | Description        |
|-----|--------------|-----|--------------------|
| 1   | Ground       | 6   | Audio In/OUT RCA   |
| 2   | VGA Port     | 7   | HDMI Port          |
| 3   | Power Input  | 8   | Video In Put Port  |
| 4   | Network Port | 9   | Video Out Put Port |
| 5   | USB Port     |     |                    |

